

Declaration of performance according to Regulation (EU) 305/2011



No. D2clift/08-2023

PRODUCT		MANUFACTURER	VERIFICATION
Type:	Wood burning insert	UNIROL sp. z o.o. Ul.Wroclawska 2A 58- 211 Uciechów Poland	Technický skúšobný ústav Piešťany, š.p. Slovenská republika
Trade name:	Dragon 2C Lift		
Intended area of use:	Heating of rooms in residential buildings		
Fluel:	Wood		

HARMONISED TECHNICAL SPECIFICATION: EN 13229:2001 / A1:2003 / A2:2004

DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	
Fire safety	+	
Fire classification	A1	
Minimum distance to flammable materials	Rear: 2000 mm Side: 2000 mm 2000 mm Floor: 2000 mm	Ceiling: Front: 2000 mm
Fire hazard due to burning fuel falling out	+	
Emissions from combustion	CO (13% O ₂)	570 mg/ m ³
	OGC (13% O ₂)	37 mg/ m ³
	NOx (13% O ₂)	52 mg/ m ³
	dust (13% O ₂)	38 mg/ m ³
Cleanability	+	
Surface temperatures	+	
Mechanical resistance	+	
Nominal output / (declared by the manufacturer)	13,9 kW / (4	
Efficiency	77,29%	
Flue gas temperature at nominal output	298,5°C	

The undersigned is responsible for the manufacture and conformity with the declared performance.

Waldemar Wuczyński, Prezes zarządu Unirol sp. z o.o.

Uciechów, 2nd August 2023